

Dimensions in Inches

Size	Item no.	Weight	L	H max.	d1	D	K	n x Ød
DN20 3/4"	106 29 46	7.5 lbs.	5.91	4.65	2.76	3.875	2.75	4 x 0.62
DN25 1"	106 29 47	7.8 lbs.	6.30	4.65	2.76	4.25	3.12	4 x 0.62
DN32 1 1/4"	106 29 48	12.8 lbs.	7.09	5.35	2.76	4.625	3.50	4 x 0.62
DN40 1 1/2"	106 29 49	13.7 lbs.	7.87	5.35	2.76	5.0	3.88	4 x 0.62
DN50 2"	106 29 50	18.6 lbs.	9.06	5.71	2.76	6.0	4.75	4 x 0.75
DN65 2 1/2"	106 29 51	31.7 lbs.	11.4	7.4	4.33	7.0	5.50	4 x 0.75
DN80 3"	106 29 52	39.8 lbs.	12.2	8.0	4.33	7.50	6.0	4 x 0.75
DN100 4"	106 29 53	61.3 lbs.	13.8	9.45	6.3	8.50	7.50	8 x 0.75
DN125 5"	106 29 54	89.9 lbs.	15.8	11.1	6.3	10.0	8.50	8 x 0.88
DN150 6"	106 29 55	113.9 lbs.	18.9	11.2	6.3	11.0	9.50	8 x 0.88
DN200 8"	106 29 56	361.9 lbs.	23.6	18.4	11.8	13.5	11.75	8 x 0.88
DN250 10"	106 29 57	431.2 lbs.	28.7	18.9	11.8	16	14.25	12 x 1.0
DN300 12"	106 29 58	581.9 lbs.	33.5	20.3	11.8	19.0	17.0	12 x 1.0
DN350 14"	106 29 59	770.0 lbs.	38.6	22.1	11.8	21.0	18.75	12 x 1.12
DN400 16"	106 29 60	1063 lbs.	43.3	25.8	11.8	23.5	21.25	16 x 1.12

Product Specification:

Oventrop double regulating and commissioning valves “Hydrocontrol F” are installed in the pipework of central hot water heating and cooling systems and serve to achieve a hydronic balance between the various circuits of the system.

The balance is achieved by a presetting with memory position. The calculated flow rate or pressure loss for each individual pipe can be preset centrally and regulated precisely. The required values of presetting can be obtained from the flow charts. All intermediate values are infinitely adjustable. The selected presetting can be read off two scales. The Oventrop double regulating and commissioning valves have two threaded ports which are equipped with the pressure test points for measuring the differential pressure. These valves are suitable for positive shutoff and balancing.

Specifications:

- Maximum working temperature: 300°F
- Maximum working pressure: 235 psi
- Temperature range: 15°F to 300°F
- Measuring Accuracy: +/- 5%

Valve bodies manufactured from cast iron to ASME/ANSI B16.5 and flanged to 125 lb. standards. Valve body made of cast iron (ASTM A48(3/4"-6"), A536(8"-16")), hole circle of the flanged connection according to ANSI 150.

- Bonnet, stem and disc made of bronze/dezincification resistant brass.
- Disc with PTFE seal.
- Double EPDM O-ring stem seal.

Installation Notes

When installing the valves, it is to be observed that the direction of flow conforms with the arrow on the valve body and that the valve is installed with a minimum of 3 D (3 x nominal pipe diameter) of straight pipe at the valve inlet and of 2 D (2 x nominal pipe diameter) of straight pipe at the valve outlet.

The double regulating and commissioning valves may be installed in either the supply or the return pipe.




Hydrocontrol F—Flanged Connection—3/4" to 12" valves
Cv Values for Various Handwheel Settings

Presetting or Handwheel Turns	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
0.0	Positive Shutoff for all sizes at "0" setting.												
0.5	0.26	0.97	0.97	1.94	3.83	2.21	2.67	3.96	6.40	6.50	-	-	-
1.0	0.49	1.55	2.01	3.80	6.70	4.19	5.12	9.94	14.48	17.70	-	-	-
1.5	0.73	2.13	3.12	5.55	8.42	6.51	8.14	16.28	22.56	29.37	-	-	-
2.0	0.97	2.72	4.22	7.21	11.10	11.63	13.78	21.51	30.93	41.00	56.86	81.4	232.56
2.5	1.21	3.29	5.33	8.59	13.45	17.44	21.69	27.91	40.41	62.70	72.09	98.84	290.70
3.0	1.45	3.86	6.43	10.10	15.59	27.91	30.35	41.16	55.52	110.49	97.67	127.91	360.47
3.5	1.79	4.63	7.57	11.59	18.09	39.53	40.70	60.47	73.66	157.50	132.56	174.42	441.86
4.0	2.33	5.51	8.67	13.23	21.33	50.58	52.03	83.72	94.24	194.33	175.58	226.74	558.14
4.5	2.95	6.51	9.85	14.99	23.90	60.47	64.19	108.14	120.41	236.80	239.53	313.95	662.79
5.0	3.59	7.72	10.99	16.87	26.40	70.93	75.12	130.23	149.13	277.80	302.67	413.95	767.44
5.5	4.22	8.65	12.33	19.33	28.84	81.41	87.73	153.29	184.53	316.74	372.09	511.63	872.09
6.0	4.85	9.19	13.60	22.24	31.26	90.70	101.16	172.09	215.47	349.30	445.35	606.98	982.56
6.5	5.30	9.53	14.90	24.30	32.92	98.84	113.43	190.73	253.55	379.88	555.58	705.81	1069.77
7.0	5.55	9.74	15.87	25.93	34.51	104.65	124.13	208.15	283.90	413.49	592.44	793.02	1151.16
7.5	-	-	16.63	27.29	35.91	109.88	133.14	220.98	311.80	444.19	650.00	883.72	1244.19
8.0	-	-	17.28	28.50	37.21	113.95	142.09	233.72	340.70	470.12	718.60	976.74	1325.58
8.5	-	-	17.93	29.26	38.44	-	-	-	-	-	767.44	1034.88	1406.98
9.0	-	-	18.57	29.97	39.60	-	-	-	-	-	842.44	1084.88	1500.00
9.5	-	-	19.22	30.63	40.70	-	-	-	-	-	881.98	1139.53	1569.77
10.0	-	-	19.86	31.26	41.86	-	-	-	-	-	894.19	1195.35	1651.16
10.5	-	-	-	-	-	-	-	-	-	-	906.98	1255.81	1720.93
11.0	-	-	-	-	-	-	-	-	-	-	918.60	1302.33	1779.07
11.5	-	-	-	-	-	-	-	-	-	-	931.86	1348.84	1825.58
12.0	-	-	-	-	-	-	-	-	-	-	947.09	1395.35	1860.47

"Hydrocontrol" Valve Accessories

 Set of 2 pressure test points
 Item 106 02 81

 Extension piece for pressure test points
 80mm Item 106 02 95

 Fill and drain ball valve 1/4"
 Item 106 01 91

 Measuring adapter
 for fill and drain ball valve
 Item 106 02 98

 Flow meter
 OV-DMC 2
 Item 106 91 77

 Insulation shell
 for "Hydrocontrol F" & "G"

Size	Item no.
DN20 3/4"	106 25 81
DN25 1"	106 25 82
DN32 1 1/4"	106 25 83
DN40 1 1/2"	106 25 84
DN50 2"	106 25 85
DN65 2 1/2"	106 25 86
DN80 3"	106 25 87
DN100 4"	106 25 88
DN125 5"	106 25 89
DN150 6"	106 25 90